

## EXP40

**Expansion Module for the SIP-T46GN and SIP-T48GN Expanding the functional capability of the above phones** Large graphic LCD

Two pages of 20 flexible buttons

Program up to 40 various features

Wall mountable



### **High-Performance LCD Expansion Module**

The EXP40 is designed to match the stylish look and feel of T46GN and T48GN with rubber feet and new foot stand allowing two positions for the device, as well as wall mountability. The backlit display eliminates the need for external light. The unit is easy to install, simply link EXP40 to the EXT port of the phone

Equipped with a 160x320 graphic LCD with Backlight, 20 physical keys each with a dual-color LED and two page views are possible. This allows 40 additional programmable keys that can be used for speed dialing, BLF/BLA, call forward, transfer, park, pickup, etc. Two independent control keys are used for fast switch between pages.

> As an attendant console application up to 6 expansion modules can be supported adding up to 240 additional buttons. More than two connections must be powered by a conventional power supply (5V/1.2A).



# EXP40

#### Display

160x320 graphic LCD with 16-level grayscales LCD Backlight

Two page views are possible Different icons for each function shown

#### Feature keys and indicators

20 physical keys each with a dual-colour LED

20 additional keys through page switch 2 independent control keys are used for fast switch between pages Programmable for shared line, BLF List, call park, conference, forward, group

group listening, LDAP, Pick UP, XML Browser

#### **Physical Features**

Wall mountable Stand with 2 adjustable angles Expansion module (≤2) is powered by

the host phone

Supports up to 6 modules daisy-chain 2xRJ12 (6P6C) ports for data in and out Dimension (W\*D\*H\*T):

127mm\*213mm\*167mm\*45mm Applies to Yealink IP Phone Operating temperature: -10~50°C Operating humidity: 10-95%

### **Packaging**

Qty/CTN: 10 PCS N.W/CTN: 6.7 kg G.W/CTN: 7.6 kg

Giftbox size: 237mm\*154mm\*100mm Carton Meas: 520mm\*317mm\*247mm

#### Certifications



**WEEE Compliant** 



**ROHS Compliant** 







