

J4858C HP Compatible 1000BASE-SX SFP Transceiver

Features

- Supports 1000BASE Ethernet
- Transmission distance up to 550m with 50/125 um MMF
- 300 meters on 62.5/125 um MMF
- Hot-Swappable if your device supports
- Lifetime Warranty
- Plugs into SFP port
- Industry-standard LC duplex connector
- Compliant to SFP Electrical & Mechanical MSA
- 0°C to +70°C case operating temperature range
- Laser Class 1 IEC / CDRH compliant
- RoHS 6/6 compliant
- Compliant with product safety standards



Product Overview

The Hummingbird Networks 100% HP Compatible J4858C optical transceiver module is for transmission at 850nm over multimode fiber. It supports Ethernet standards which make it ideally suited for 1000BASE-SX data communications. It offers customers a wide variety of Gigabit Ethernet connectivity options for data center, enterprise wiring closet, and service provider transport applications.

Its sub watt power consumption and its excellent EMI performance allow system design with high port density. The small form factor integrates an 850nm vertical cavity surface emitting laser (VCSEL) in an LC package and the receiver section uses an integrated GaAs detector preamplifier (IDP). Module is lead free, RoHS compliant and is designed and tested in accordance with industry safety standards.

Ordering Information

Part No.	Data Rate	Laser	Fiber Type	Distance	Optical Interface	DDMI
J4858C-HN	1.25Gbps	850nm	MMF	550m	LC	YES

Supported Standards

Application	Standard	Data Rate
Gigabit Ethernet	1000BASE-SX	1.25Gbps

Optical Characteristics

Parameter	Conditions	Min Modal Bandwidth (MHz*km)	Symbol	Units
Operating Range	62.5 μm MMF	300	IOP	m
	50 μm MMF	550		

Digital Optical Monitoring

Transceivers offer the ability to monitor important module parameters during operation. The temperature, supply voltage, laser bias current, optical transmitter power and receiver optical power parameters are continuously monitored for getting information about the module's current status. All data is calibrated internally; there is no need for external post processing.

Regulatory Compliance

The J4858C modules are designed to meet international requirements and standards in terms of product safety. The modules optical output power meets Class 1 requirements for laser safety.

Feature	Standard	Performance
Electrostatic Discharge (ESD) to the Electrical Pins	MIL-STD-883E Method 3015.7	Class 1(>500 V) Isolation with the case
Electromagnetic Interference	FCC Part 15 Class B	Compatible with standards
Laser Eye Safety	FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2	Compatible with Class I laser product. Compatible with T V standards
Component Recognition	UL and CUL	UL file E317337
Green Products	RoHS	RoHS6

Additional Information

For more information about our compatible SFP modules, contact:

Hummingbird Networks

sales@hummingbirdnetworks.com

Tel: 1-866-551-3278

www.hummingbirdnetworks.com